



THB.392.A4A.L

MADE IN ITALY



TH392 - Circular mini-junction connector 4 ways type "H" IP68

NEW



GENERAL DESCRIPTION

| | |
|--------------------------|--|
| Type of installation | Joint connector (re-usable/re-accessible) |
| Type of product (Family) | TEETUBE® - In-line and junction circular connectors IP68/IP69K |
| Product name (Series) | TH392 - Circular mini-junction connector 4 vie tipo "H" IP68 |
| Product configuration | In-line joint connector |
| Colour | Black (Plastic components) - Techno green (Rubber components) |
| Outer dimension | 28 mm x 54 mm x 109 mm |

ELECTRICAL CHARACTERISTICS

| | |
|--------------------|--------------------------|
| Number of poles | 4 |
| Contact marking | 1 - 2 - 3 - 4 |
| Type of connection | screw (M3 - max. 0.8 Nm) |
| Operating current | max. 17.5A |
| Operating voltage | max. 450V AC |

MECHANICAL CHARACTERISTICS

| | |
|-------------------------------------|------------------------------------|
| Protection against solid/water (IP) | IP68 (30m/2h) |
| Corrosion resistance | Salt mist test : EN60068-2-11:2000 |

CABLE CHARACTERISTICS

| | |
|---|---|
| Wire cross-section min. - max. (Stranded cable) | 0.5 mm ² - 4.0 mm ² |
| Cable diameter min. - max. | 7.0 mm - 13.5 mm |

MATERIAL CHARACTERISTICS

| | |
|-----------------------------|------------------------------|
| Connector housing | PA68 UL94 V0 GWT 960° |
| Cable gland | PA66 UL94 V2 GWT 850°C |
| Sealing | TPE |
| Grommets | TPE |
| Contacts | CuZn (nickel plated) |
| Screws | Steel (rivestimento Zinco) |
| Material properties | Halogen Free - Silicone Free |
| T marking | T 85°C |
| Operating temperature range | -40°C / +125°C |
| Proof Tracking Index (PTI) | PTI 250 |

INDUSTRY STANDARDS

| | |
|-----------------|-----------------|
| Standard number | EN 60998-1:2004 |
|-----------------|-----------------|

PACKAGING INFORMATION

| | |
|------------------------|--------------------------|
| Packaging method | not assembled components |
| Quantity (product/box) | 50 pz |
| Unit weight | 95,0 |
| Box dimension | 400x210x170 mm |



INSTALLATION INSTRUCTIONS

- Guidelines Installation PDF • 753 KB
- 606004100 IST TH392 nuovo NEW
PDF • 1 MB
- 606004100 IST TH392 nuovo Lungo NEW
PDF • 695 KB

CERTIFICATIONS AND TEST REPORTS

- TH392 CA0205752 resinato PDF • 290 KB
- CE-TH392 DOCX • 352 KB
- TH392 CA0205251 PDF • 1 MB

MARKETING COLLATERALS

- X DRY A4 ita 2 PDF • 76 KB
- cartolina 210x105 ita 2 PDF • 82 KB
- Cameriere pag intera PDF • 2 MB
- Pannello 3 PDF • 457 KB